ARTIFACT SHEET

	artifact type code (see list below) + sequential letter (A, B, C). The first
	artifact folder for an artifact type receives the letter A, the second B, etc
	Examples: 59123456PA, 59123456PB, 59123456ZA, 59123456ZB
	19186260 BA
	Indicate quantity of a single type of artifact received but not scanned. Create individual artifact folder/box and artifact number for each Artifact Type.
	CD(s) containing:
	computer program listing
	Doc Code: Computer Artifact Type Code: P pages of specification
	and/or sequence listing
	and/or table
	Doc Code: Artifact Artifact Type Code: S
	content unspecified or combined
	Doc Code: Artifact Artifact Type Code: U
	Stapled Set(s) Color Documents or B/W Photographs
	Doc Code: Artifact Type Code: C
	Microfilm(s)
	Doc Code: Artifact Type Code: F
	Video tape(s)
	Doc Code: Artifact Artifact Type Code: V
	Model(s)
•	Doc Code: Artifact Type Code: M
	Round Dooumont(a)
	Bound Document(s) Doc Code: Artifact Artifact Type Code: B
	Boe code. Attract Type code. B
	Confidential Information Disclosure Statement or Other Documents
	marked Proprietary, Trade Secrets, Subject to Protective Order,
	Material Submitted under MPEP 724.02, etc.
	Doc Code: Artifact Type Code X
	Other, description:
	Doc Code: Artifact Artifact Type Code: 7

The United States America



The Commissioner of Patents and Trademarks

Has received an application for a patent for a new and useful invention. The title and description of the invention are enclosed. The requirements of law have been complied with, and it has been determined that a patent on the invention shall be granted under the law.

Therefore, this

United States Patent

Grants to the person(s) having title to this patent the right to exclude others from making, using, offering for sale, or selling the invention throughout the United States of America or importing the invention into the United States of America for the term set forth below, subject to the payment of maintenance fees as provided by law.

If this application was filed prior to June 8, 1995, the term of this patent is the longer of seventeen years from the date of grant of this patent or twenty years from the earliest effective U.S. filing date of the application, subject to any statutory extension.

If this application was filed on or after June 8, 1995, the term of this patent is twenty years from the U.S. filing date, subject to any statutory extension. If the application contains a specific reference to an earlier filed application or applications under 35 U.S.C. 120, 121 or 365(c), the term of the patent is twenty years from the date on which the earliest application was filed, subject to any statutory extension.

Lence Tedman

Dandra Amorta



4514AدەUS005

United States Patent [19]

Gipson

[11] Patent Number:

5,839,514

[45] Date of Patent:

Nov. 24, 1998

[54]	METHOD AND APPARATUS FOR	
	INJECTION OF TUBING INTO WELLS	

[75] Inventor: Thomas C. Gipson, Cisco, Tex.

[73] Assignee: Fleet Cementers, Inc., Cisco, Tex.

[21] Appl. No.: 862,745

[22] Filed: May 23, 1997

166/85.5, 384, 385; 242/399.1, 399.2, 596.3; 254/281, 288, 326, 332, 333

[56]

References Cited

U.S. PATENT DOCUMENTS

3,116,793	1/1964	McStravick	166/77.2 X
3,841,407	10/1974	Bozeman	166/77.3 X
4,249,600	2/1981	Bailey	166/77.2
4,553,590	11/1985	Phillips	254/332 X

4,673,035	6/1987	Gipson 166/77.2
		Gipson 166/50 X
		Sola 166/77.2 X
5.765.643	6/1998	Shaaban et al 166/384


Primary Examiner—George Suchfield Attorney, Agent, or Firm—Miller. Sisson, Chapman & Nash, P.C.

ABSTRACT

[57]

An improved apparatus and method for injecting and retrieving a length of coiled tubing and storing the tubing on a storage spool. An injector reel is pivotally mounted on a frame such that coiled tubing may be angularly injected to shallow, horizontal wells. A hold-down assembly is provided to individually adjust the pressure applied to the coiled tubing as it is injected into or retrieved from a well. The positioning of the injector reel and the storage spool in the injecting mode ensures a greater degree of wrapping of the coiled tubing around the injector reel to improve the control of the injection and retraction of the tubing. A vertically and horizontally adjustable storage spool cradle enables the operator to vary the width and diameter of the storage spools used in the apparatus.

11 Claims, 8 Drawing Sheets



nd of